

	Project		Job no.				
1	В	aker's Lane, Ch	artham, CT4 7C)B	301817		
	Calcs for		Start page no./Revision				
		Soakawa	1				
	Calcs by	Calcs date	Checked by	Checked date	Approved by	Approved date	
	MW	22/05/2018	PB				

SOAKAWAY DESIGN

In accordance with BRE Digest 365 - Soakaway design

Tedds calculation version 2.0.03

Design rainfall intensity

Location of catchment area Other

 $\label{eq:main_eq} \begin{array}{ll} \mbox{Impermeable area drained to the system} & \mbox{A} = \mbox{145.0 m}^2 \\ \mbox{Return period} & \mbox{Period} = \mbox{100 yr} \end{array}$

Ratio 60 min to 2 day rainfall of 5 yr return period r = 0.450

5-year return period rainfall of 60 minutes duration M5_60min = **20.0** mm

Increase of rainfall intensity due to global warming polimate = 40 %

Soakaway / infiltration trench details

Soakaway type Rectangular Minimum depth of pit (below incoming invert) d = 800 mm Width of pit w = 2754 mm Length of pit l = 2000 mm Percentage free volume $V_{\text{free}} = 95 \%$ Soil infiltration rate $f = 370. \times 10^{-6} \text{ m/s}$

Wetted area of pit 50% full $a_{s50} = I_{\times}d + w_{\times}d = 3803140 \text{ mm}^2$

Table equations

Inflow (cl.3.3.1) $I = M100 \times A$ Outflow (cl.3.3.2) $O = a_{\$50} \times f \times D$ Storage (cl.3.3.3) S = I - O

Duration, D (min)	Growth factor Z1	M5 rainfalls (mm)	Growth factor Z2	100 year rainfall, M100 (mm)	Inflow (m³)	Outflow (m³)	Storage required (m³)
5	0.39;	10.9;	1.92;	21.0;	3.05;	0.42;	2.63
10	0.54;	15.1;	1.99;	30.1;	4.36;	0.84;	3.52
15	0.65;	18.2;	2.02;	36.7;	5.32;	1.27;	4.05
30	0.82;	23.0;	2.02;	46.3;	6.72;	2.53;	4.19
60	1.00;	28.0;	1.99;	55.6;	8.06;	5.07;	3.00
120	1.19;	33.3;	1.94;	64.8;	9.39;	10.13;	0.00
240	1.38;	38.6;	1.90;	73.5;	10.65;	20.26;	0.00
360	1.51;	42.3;	1.87;	79.1;	11.48;	30.39;	0.00
600	1.68;	47.0;	1.83;	86.3;	12.51;	50.66;	0.00
1440	2.03;	56.8;	1.76;	100.2;	14.53;	121.58;	0.00

Required storage volume $S_{req} = 4.19 \text{ m}^3$

Soakaway storage volume $S_{act} = I_{\times} d_{\times} w_{\times} V_{free} = 4.19 \text{ m}^3$

PASS - Soakaway storage volume

Time for emptying soakaway to half volume $t_{s50} = S_{req} \times 0.5 \ / \ (a_{s50} \times f) \ = 24 min \ 49 s$

PASS - Soakaway discharge time less than or equal to 24 hours